

Bảng thông số sản phẩm

Thông số kỹ thuật



APC Easy UPS, 700VA, Tower, 230V, 2 Universal outlets, AVR, 1 USB Type A Port

BVX700LUI-MS

Overview

Lead Time Usually in Stock

Main

Main Input Voltage	230 V AC 1 phase
Main Output Voltage	230 V AC 1 phase
Rated Power In W	360 W
Rated Power In Va	700 VA
Input Connection Type	IEC 60320 C14
Output Connection Type	2 universal
Cable Length	1.22 m
Number Of Cables	1
Battery Type	Lead-acid battery
Provided Equipment	User manual

Batteries & Runtime

Thời Gian Chạy	View Runtime Graph
Hiệu Suất	View Efficiency Graph
Number Of Battery Filled Slots	0
Number Of Battery Free Slots	0
Battery Recharge Time	8 h
Battery Voltage	12 V
Battery Capacity	7.0 Ah
Battery Life	2...3 year(s)
Replacement Battery	APCRBC110
Extended Runtime	0

General

Max Runtime	120 min
Number Of Power Module Free Slots	0
Number Of Power Module Filled Slots	0
Redundant	No

Ups Size	WS
----------	----

Physical

Colour	Black
Height	13.8 cm
Width	9.8 cm
Depth	31 cm
Net Weight	4.2 kg
Mounting Support	Floor
Mounting Preference	No preference
Mounting Mode	Not rack-mountable
Two Post Mountable	0
Usb Compatible	No

Input

Network Frequency	50/60 Hz +/- 5 Hz auto-sensing
Input Voltage Limits	170...280 V 230 V AC
Cos Phi	0.51

Output

Maximum Configurable Power In W	360 W
Output Frequency	50/60 Hz +/- 1 Hz sync to mains
Ups Type	Line interactive
Wave Type	Stepped approximation to a sinewave
Full Load Runtime	00:00:01 360 W
Graph Display	1
Half Load Runtime	00:06:00 180 W
Maximum Configurable Power In Va	700 VA
Transfer Time	6 ms typical : 10 ms maximum

Conformance

Product Certifications	CE CB
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018
Equipment Protection Policy	Lifetime : 50000 euros

Environmental

Ambient Air Temperature For Operation	0...40 °C
Relative Humidity	0...95 % non-condensing
Operating Altitude	0...3000 m
Ambient Air Temperature For Storage	-15...40 °C

Storage Relative Humidity	0...95 % non-condensing
Storage Altitude	0...3000 m
Acoustic Level	40 dBA
Ip Degree Of Protection	IP20

Surge Protection and Filtering

Surge Energy Rate	273 J
--------------------------	-------

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	22.2 cm
Package 1 Width	34.6 cm
Package 1 Length	14.2 cm
Package 1 Weight	4.5 kg
Scc14	10731304417610

Contractual warranty

Warranty	2 years repair or replace
-----------------	---------------------------

Bền vững

Nhãn **Green Premium™** là cam kết của Schneider Electric trong việc cung cấp sản phẩm với hiệu suất môi trường tốt nhất. Green Premium cam kết tuân thủ các quy định mới nhất, minh bạch về tác động môi trường, cũng như các sản phẩm tuần hoàn và CO₂ thấp.

Hướng dẫn đánh giá tính bền vững của sản phẩm là tài liệu kỹ thuật phổ thông giúp làm rõ các tiêu chuẩn nhãn sinh thái toàn cầu và cách diễn giải việc khai báo môi trường.

[Tìm hiểu thêm về Green Premium >](#)

[Hướng dẫn đánh giá về sự bền vững của sản phẩm >](#)



Minh bạch RoHS/REACH

Hiệu suất sức khỏe

Toxic Heavy Metal Free

Mercury Free

Rohs Exemption Information [Yes](#)

Chứng nhận & Tiêu chuẩn

Reach Regulation

[REACH Declaration](#)

Eu Rohs Directive

Compliant

[EU RoHS Declaration](#)

China Rohs Regulation

[China RoHS declaration](#)

Pro-active China RoHS declaration (out of China RoHS legal scope)

Environmental Disclosure

[Product Environmental Profile](#)

Weee

The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Circularity Profile

[End of Life Information](#)