


Bảng thông số sản phẩm

Thông số kỹ thuật



APC Back-UPS 1400VA, 230V, AVR, Universal and IEC Sockets

BX1400U-MS

⚠️ Ngày sản xuất vào: 1 thg 4, 2022

⚠️ Ngày cung cấp dịch vụ vào: 12 thg 11, 2022

⚠️ Ngày sản xuất

Overview

Lead Time Usually in Stock

Main

Main Input Voltage	230 V
Rated Power In W	700 W
Rated Power In Va	1400 VA
Output Connection Type	2 IEC 60320 C13 4 universal receptacle
Cable Length	1.22 m
Number Of Cables	2
Battery Type	Lead-acid battery

Batteries & Runtime

Thời Gian Chạy	View Runtime Graph
Hiệu Suất	View Efficiency Graph
Number Of Battery Filled Slots	1
Number Of Battery Free Slots	0
Battery Recharge Time	8 h
Number Of Battery Replacement Quantity	1
Battery Charger Power	21 W rated
Battery Life	2...5 year(s)
Replacement Battery	APCRBC113
Extended Runtime	0

General

Provided Equipment	1, detachable 1.8 m IEC power cord 1, detachable 2.0 m NEMA 5-15P to IEC C13 power cord user manual warranty card
Product Web Sub-Family	Entry level
Number Of Power Module Free Slots	0
Number Of Power Module Filled Slots	0

Redundant	No
-----------	----

Physical

Colour	Black
Height	21.5 cm
Width	13 cm
Depth	33.6 cm
Net Weight	12 kg
Mounting Preference	No preference
Mounting Mode	Not rack-mountable
Two Post Mountable	0
Usb Compatible	Yes

Input

Network Frequency	50/60 Hz +/- 3 Hz auto-sensing
Input Voltage Limits	150...280 V
Maximum Input Current	6 A
Switching Current Capacity	10 A
Input Protection Type	3-pole circuit breaker
Input Current	6 A (1 phase)
Input Power Factor At Full Load	0.5

Output

Maximum Configurable Power In W	700 W
Output Frequency	50/60 Hz +/- 1 Hz sync to mains 50/60 Hz +/- 1 Hz unsynchronised
Ups Type	Line interactive
Wave Type	Stepped approximation to a sine wave
Maximum Configurable Power In Va	1400 VA
Transfer Time	8 ms typical : 10 ms maximum

Conformance

Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018
Equipment Protection Policy	No EPP for ASEAN

Environmental

Ambient Air Temperature For Operation	0...40 °C
Relative Humidity	0...95 % non-condensing
Operating Altitude	0...10000 ft
Ambient Air Temperature For Storage	-15...45 °C
Storage Relative Humidity	0...95 % non-condensing

Storage Altitude	0.00...9144.00 m
-------------------------	------------------

Acoustic Level	45 dBA
-----------------------	--------

Communications & Management

Control Panel	LED status display with on line : on battery : replace battery and overload indicators
----------------------	--

Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
--------------	--

Surge Protection and Filtering

Surge Energy Rate	273 J
--------------------------	-------

Packing Units

Unit Type Of Package 1	PCE
-------------------------------	-----

Number Of Units In Package 1	1
-------------------------------------	---

Package 1 Height	29.5 cm
-------------------------	---------

Package 1 Width	44 cm
------------------------	-------

Package 1 Length	24.5 cm
-------------------------	---------

Package 1 Weight	12.94 kg
-------------------------	----------

Scc14	10731304315947
--------------	----------------

Contractual warranty

Warranty	2 years repair or replace
-----------------	---------------------------

Bền vững

Nhãn **Green Premium™** là cam kết của Schneider Electric trong việc cung cấp sản phẩm với hiệu suất môi trường tốt nhất. Green Premium cam kết tuân thủ các quy định mới nhất, minh bạch về tác động môi trường, cũng như các sản phẩm tuần hoàn và CO₂ thấp.

Hướng dẫn đánh giá tính bền vững của sản phẩm là tài liệu kỹ thuật phổ thông giúp làm rõ các tiêu chuẩn nhãn sinh thái toàn cầu và cách diễn giải việc khai báo môi trường.

[Tìm hiểu thêm về Green Premium >](#)

[Hướng dẫn đánh giá về sự bền vững của sản phẩm >](#)



Sử dụng hiệu quả năng lượng Take-back Minh bạch RoHS/REACH

Hiệu suất tài nguyên

Energy Efficient Product

Take-Back Program Available

Hiệu suất sức khỏe

Mercury Free

Rohs Exemption Information Yes

Chứng nhận & Tiêu chuẩn

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile [End of Life Information](#)